


N 50, GAS HOB, 60 CM, STAINLESS STEEL
T26BB59N0



Z2480X0 Simmer plate
Z32SE10X0 Small pot support
Z32SW10X0 Wok ring

Gas hob with front controls - for easy control of the 4 gas burners.

- ✓ Stainless steel surface
- ✓ black cast iron pan supports with protective rubber feet
- ✓ Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- ✓ Ignition via control dials: just push and turn the dials to ignite the flame.
- ✓ 4 burner hob

Product name/family:gas hob w
integrated controls
Built-in / Free-standing: Built-in
Energy input: Gas
Number of cooking zones: 4
Type of control setting devices: sword knobs
Min. required niche size for installation (HxWxD): .. 45 x 560-562 x
480-492 mm
Width of the appliance:582 mm
Dimensions: 53x582x520 mm
Dimensions of the packed product (HxWxD): . 141 x 651 x 578 mm
Net weight: 10.1 kg
Gross weight: 11.0 kg
Residual heat indicator:without
Location of control panel: Front
Basic surface material: Stainless steel
Color of surface:Stainless steel
Length electrical supply cord: 100.0 cm
EAN code:4242004236665
Gas connection rating:7800 W
Fuse protection:3 A
Voltage:220-240 V
Frequency:50; 60 Hz



N 50, GAS HOB, 60 CM, STAINLESS STEEL
T26BB59N0

Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet

Usage convenience

- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 burner hob
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: WOK burner up to 3.3 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 582 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.8 KW

N 50, GAS HOB, 60 CM, STAINLESS STEEL
T26BB59N0

